

## JP 4327214

8/3,AB,LS/1 (Item 1 from file: 351)  
DIALOG(R)File 351:Derwent WPI  
(c) 2004 Thomson Derwent. All rts. reserv.

009302474

WPI Acc No: 1992-429883/ 199252

XRAM Acc No: C92-190960

Composite fibre for industrial materials, e.g. bag filter scrim ground fabric - comprises three layers of PET component, polyphenylene sulphide in outermost layer and intermediate layer

Patent Assignee: TORAY IND INC (TORA )

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 4327214	A	19921116	JP 9199070	A	19910430	199252 B

Priority Applications (No Type Date): JP 9199070 A 19910430

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 4327214	A		5	D01F-008/16	

Abstract (Basic): JP 4327214 A

Composite fibre comprises 3 layers consisting of a PET component having more than 0.5 of limiting viscosity (etg) in the most inner layer, a polyphenylene sulphide (PPS) component in the most outer layer, and the intermediate layer blended with the PET component and the PPS component blended with each other.

Proportion of the most outer layer occupied in whole of the composite fibre is more than 10 wt.%. Proportion of the most inner layer occupied in whole of the composite fibre is more than 20 wt.%. Proportion of the intermediate layer occupied in whole of the fibre is less than 70 wt.%. Strength of the composite fibre is more than 5.5 g/de.

USE/ADVANTAGE - For industrial materials e.g. bag filter scrim ground fabric, motor knot braid, motor binder tape and fibre for reinforcing rubber. The composite fibre has excellent heat resistance, chemical resistance, greatly improved peeling resistance, and esp. excellent fatigue resistance.

Dwg.0/0